2005 DOE Hydrogen Program Review

Controlled Hydrogen Fleet and Infrastructure Demonstration and Validation Project

TEAM: ChevronTexaco Technology Ventures Hyundai-Kia Motor Company UTC Fuel Cells

Rajesh Paulose – Project Director

John Brady – Business Officer

ChevronTexaco Technology Ventures LLC.

May 2005

Project ID TV11



This presentation does not include any proprietary or confidential information.



Overview

Timeline

January 15, 2004 September 30, 2009

< 5% completed

Barriers

Peformance		2008	2015
Measure	Units	Target	Target
Fuel Cell Stack	Hours	2000	5000
Range	Miles	250	300
H ₂ Cost	\$/kg	\$3.00	\$1.50

Budget

Total project funding - \$93.9 mil

✓DOE share = \$37.8 mil

✓Contractor share - \$56.1 mil

Funding FY04 - \$3.0 mil

Funding FY05 - \$0.7 mil



Team Members

- Hyundai-Kia Motor Companies
- UTC Fuel Cells
- Hyundai Kia America Technical Center
- Alameda Contra Costa Transit
- Southern California Edison

Objectives

- To better understand how fuel cell vehicles and hydrogen infrastructure can be designed to work together to fuel vehicles of the future.
- To understand how an average individual would react to a fuel cell car / hydrogen energy station.
- Compare different methods of hydrogen generation along with the use of stationary fuel cells to co-generate power.
- Test the impact of different climatic conditions on fuel cell cars.
- Assist in the development of research for use in important safety and legal codes and standards.



Approach - Infrastructure

• Up to six fueling stations using different types of hydrogen generation technologies.

✓Ranges from natural gas reforming to electrolyzers

• Some stations may deploy stationary fuel cells to study overall station balance and grid interconnections.



Approach -FCVS

- 32 fuel cell SUVs Hyundai Tuscon and Kia Sportage, both powered by UTC fuel cells
- Three climatic conditions hot, mild and cold weather sites.
- To increase range, two generations of hydrogen storage tank will be tested on the vehicles, 350 bar and 700 bar.
- Other planned generational differences are:
 - Cost reduction of key components
 - Increased reliability of BOP components
 - ✓ Increased reliability of fuel cell power train system



Progress / Results - Infrastructure

- First of up to six the six hydrogen stations deployed at Chino, CA
 - Reforms natural gas using the auto thermal reforming (ATR) process.
 - Station is capable of producing 15 kg of hydrogen per day and has a storage capacity of 105 kg.
 - Station is capable of dispensing 5,000 psig to two vehicles simultaneously
 - As part of station development, several training sessions were held for first responders.
 - Station received Canadian Standards Association (CSA) approval.
 - Station now has the final permit to operate.
 - Currently the station is undergoing various commissioning steps.



Progress / Results - Vehicle

- Finished building 2 of the 32 fuel cell SUVs
 - These cars are currently undergoing road trials in Korea
 - These cars are scheduled to arrive at Chino, CA in late May where they will undergo further testing before being introduced into fleet operation.
 - ✓ Up to 7 additional cars in 2005
 - ✓ All material on order or received for 2005 deliveries
 - ✓ Data Collection system developed/validated in 2005
 - Hydrogen safe workshop to provide maintenance and service for fleet vehicles in 2005



Future Work - Infrastructure

- Engineering design work for next hydrogen station, at Rosemead, CA, well underway.
 - ✓ Rosemead station will use an alkaline electrolyzer
- Engineering design of future stations is being developed on site-appropriate timeline.



Future Work -FCVS

- Engineering consideration and development for FCV Test
 - ✓ Hydrogen safe Chassis Dyno facility in 2005
 - ✓ Baseline test for the first generation FCV in 2005





BACKUP SLIDE #1 Hydrogen Safety - Infrastructure

- We currently believe that one of the most significant hydrogen hazards associated with the Chino facility (already built for this project) is:
 - The unplanned and uncontrolled release of high pressure hydrogen (e.g. from storage or dispensing), which carries with it risk to equipment and personnel.





BACKUP SLIDE #2 Hydrogen Safety - Infrastructure

- Our current approach to deal with this hazard scenario is:
 - To design equipment according to code, including safety instrumentation/controls (e.g. pressure relief device, gas sensors, etc).
 - To procure equipment from vendors with experience in high pressure hydrogen.
 - ✓ To install equipment according to code and permits.
 - To insure site commissioning and testing procedures are developed and implemented before putting site into full operation.
 - To insure Operation & Maintenance programs (e.g. Safe Work Practices, Operator Training for vehicle dispensing) are developed according to vendor recommendation and company practice



BACKUP SLIDE #3 Hydrogen Safety -FCVS

- We have designed the fuel cell vehicles to contain redundant mechanisms to ensure hydrogen safety.
 - Active ventilation system ensures the concentration of the exhaust hydrogen under 25% of the lower flammable limit of hydrogen.
 - The crash sensors to detect impacts at the front and rear of the vehicle.
 - Safety design consideration of its location for the hydrogen sensors in the cabin, fuel cell plant and around the fuel storage system.

