

Validation of an Integrated Hydrogen Energy Station

Project ID: TV-06

Greg Keenan

Air Products and Chemicals, Inc.

May 18, 2006

This presentation contains no confidential information




FuelCell Energy

AIR
PRODUCTS 

The Air Products logo, consisting of the word "AIR" above "PRODUCTS" in a bold, sans-serif font, followed by a stylized logo icon of a triangle with horizontal lines.

Hydrogen Energy Station Vision



Objectives

- Overall Project
 - To demonstrate the economic and technical viability of a hydrogen energy station using a high temperature fuel cell designed to produce power and hydrogen
 - Maintain safety as a top priority in the system design and operation
- Past Year
 - Completed Phase 2- System Design
 - Phase 3 Go / No-Go Decision
 - Submitted Continuation Application

Objectives by Phase

- Phase 1A- Evaluated PEM (Completed FY03)
- Phase 1B- Evaluation of HTFC Coproduction (Completed FY04)
 - Co-production efficiencies: 55%-60% (LHV)
 - Potential to meet the DOE targets while producing power for less than 0.10 \$/kW
- ✓ • Phase 2- System Design In Progress (In Progress)
 - Select Fuel Cell Technology
 - Engineering Development
 - GO / No-GO Decision
- Phase 3: Detailed Design and Construction (FY06 – 07)
- Phase 4: Operation, Testing, Data Collection (FY07 – 08)

Overview: Budget

- **Total Project Budget:**
 - \$1,446,877
- **Cost Sharing:**
 - DOE - \$723,438
 - APCI and Partners – balance.
- **FY2005 Total Spend**
 - \$413,866 k
- **FY2006 DOE Funding**
 - \$1,620,086 (Pending Approval)

Overview: Technical Barriers and Targets

- **DOE Technical Barriers**
 - **Technical Validation (Section 3.5.4 of HFCIT Program Report), Task #4.**
 - B. Storage
 - C. H₂ Refueling Infrastructure
 - I. Hydrogen and Electricity Coproduction
- **DOE Targets**
 - **H₂ Production (Table 3.1.2 of HFCIT Program Report), Task #3.**
 - Cost of H₂:
 - \$3/kg 2005
 - \$1.50/kg 2010
 - **Energy Station Coproduction of H₂ and Electricity (Table 3.1.2, Task #4)**
 - Durability > 40,000 hours
 - Electrical Efficiency > 40%

Distributed Power and Hydrogen

FuelCell Energy DFC-300



50%
Power

15%
Heat




20%
H₂



Phase 2 Plan

- **Engineering Design and Development**
 - **Detailed Engineering Development, Design, and Cost Estimate**
 - Anode Gas Handling (FCE)
 - Hydrogen Purification (APCI)
 - Integration (APCI & FCE)
 - **Economics Updated**
- **Phase 3 Go - No-Go Decision**

Hydrogen Coproduction using MCFC



- Heat Recovery
- Water Gas Shift
- Cooling and Water Recovery
- Compression
- Hydrogen Recovery
- Tailgas Integration

Anode Gas Handling

- Evaluated design options for processing anode exhaust
- Assessed safety and control requirements for integrating DFC power plants with APCI subsystem for H₂ separation
- Developed preliminary P&ID
- Sized processing equipment
- Completed cost estimates
- Developed preliminary layout
- Tested critical components

FCE Component Testing

- Fuel Cell Operation at H₂ Export Design Conditions
- Electrolyte Filter
- Heat Exchanger Train
- Shift Reactor

Purification Development Program

- Investigated over 25 different hydrogen separation and purification technologies
- Selected Pressure Swing Adsorption Process for further Development
 - Cycle Simulation Completed
 - Adsorbent Mix Selected
 - Lab Testing Completed
 - Pilot Plant Verification Completed
 - Optimized PSA system
 - Patent Applications in Progress


Purification System Design

- PSA System Design Completed- PFD, P&ID, H&MB
- Compressor Specified and Selected
- Process Control Strategy Developed
- Equipment Quotes and Fabrication Estimates Completed
- Installation Costs Estimated

Integration

- PFD
- H&MB
- Plot Plan
- Technical Risk Plan
- Preliminary Hazop
- Process Control Strategy
- Start-up / Shutdown Plan
- Installation /Construction
- Testing Strategy
- Security Review

Hydrogen Energy Station



Projected Performance

	Units	Phase I
Overall Efficiency <small>(Net Power + Hydrogen Product) / (Fuel)</small>	LHV	60%
Power Efficiency <small>Net Power / (Total Fuel – Hydrogen Product)</small>	LHV	49%
Hydrogen Efficiency <small>(Hydrogen Product – Purification Power) / Hydrogen Product</small>	LHV	68%
Hydrogen Product	Nm ³ /hr	~ 40
Net Power w/o & w Hydrogen	kW	~ 247 / 207
Natural Gas Flow	Nm ³ /hr	~ 55


Projected Performance

	Units	Phase I	Phase II
Overall Efficiency <small>(Net Power + Hydrogen Product) / (Fuel)</small>	LHV	60% →	66%
Power Efficiency <small>Net Power / (Total Fuel – Hydrogen Product)</small>	LHV	49%	49%
Hydrogen Efficiency <small>(Hydrogen Product – Purification Power) / Hydrogen Product</small>	LHV	68% →	77%
Hydrogen Product	Nm ³ /hr	~ 40 →	~ 80
Net Power w/o & w Hydrogen	kW	~ 247 / 207	~ 300 / 243
Natural Gas Flow	Nm ³ /hr	~ 55	~ 74

Economics: Assumptions

- Project Life: 15 Years
- Depreciation: 15 Years
- Inflation: 1.9%
- Tax Depreciation: 5 Year MACRS
- DCF Return: 10%
- Overheads: 20%
- Taxes: 37.8%
- Maintenance: Bottom Up Estimation

Hydrogen Energy Station Economics



Product Profile: 1200 kW Power / 700 kg/day hydrogen

Future Work

- Execute Phase III
 - Order Equipment
 - Fabricate Skids
 - Assemble and Test Complete System at FCE
 - Go-No Go for Phase 4 (18 months)
- Phase IV (FY 2008)
 - Install at Selected Site
 - 12 Month Demonstration

Response to Reviewers Questions

- “Baloney! The numbers presented were theoretical and not bottoms up analytical...”
- “The Results need to indicate whether this is an economically-viable approach to H2 Production in the long term”
- “Public condemnation as waste and abuse of DOE funds. This is a blatant attempt to use gov’t money for incremental product/system improvements to the sole benefit of APCI and FCE.”

Thank you