



Advanced Hydrogen Liquefaction Process

Funding Opportunity Number: DE-PS36-07GO97009



Joe Schwartz
Praxair - Tonawanda, NY



DOE Annual Merit Review Meeting
June 11, 2008

Copyright © 2008 Praxair Technology, Inc.

This paper was written with support of the U.S. Department of Energy under Funding Opportunity No. DE-PS36-07GO97009. The Government reserves for itself and others acting on its behalf a royalty-free, nonexclusive, irrevocable, worldwide license for Governmental purposes to publish, distribute, translate, duplicate, exhibit and perform this copyrighted paper. This presentation does not contain any proprietary or confidential information.



DOE Hydrogen Program

Project ID
PDP-31


Introduction



2008 Budget

| | Requested | Spent Through 4/15/08 |
|--------------|------------------|--------------------------|
| DOE | \$ 99,712 | \$ 0 |
| Praxair | \$ 24,928 | \$ 0 |
| TOTAL | \$124,640 | \$ 0 |

Program Timeline



➤ Phase I - Feasibility

- 1 Develop Alternative Hydrogen Liquefaction Processes
- 2 Validate Ortho-Para Conversion Process Performance

➤ Phase II - Hydrogen Liquefaction Process Development

- 3 Establish Efficiency, Equipment, and Material Performance Targets
- 4 Estimate Capital Cost

➤ Phase III – Process Performance Evaluation

- 5 Demonstrate Improved Ortho-Para Conversion Process
- 6 Evaluate Potential Cost Reduction and Efficiency Improvement

Barriers Addressed

➤ C. High Cost and Low Energy Efficiency of Hydrogen Liquefaction

- Reduced capital cost
- Improved efficiency
- Improved overall process by integration

Objectives



- **Program - Develop a low-cost hydrogen liquefaction system for 30 and 300 tons/day that meets or exceeds DOE targets for 2012**
 - Improve liquefaction energy efficiency
 - Reduce liquefier capital cost
 - Integrate improved process equipment invented since last liquefier was designed
 - Continue ortho-para conversion process development
 - Integrate improved ortho-para conversion process
 - Develop optimized new liquefaction process based on new equipment and new ortho-para conversion process
- **Phase I – Feasibility**
 - Develop conceptual designs for improved processes
 - Validate ortho-para conversion process performance

Hydrogen Liquefaction Targets



| Category | 2005 Status | 2012 | 2017 |
|--|-------------|--------|--------|
| <i>Small-Scale Liquefaction (30,000 kg H₂/day)</i> | | | |
| Installed Capital Cost (\$) | \$50M | \$40M | \$30M |
| Energy Efficiency (%) | 70% | 75% | 85% |
| <i>Large-Scale Liquefaction (300,000 kg H₂/day)</i> | | | |
| Installed Capital Cost (\$) | \$170M | \$130M | \$100M |
| Energy Efficiency (%) | 80% | >80% | 87% |

$$\text{Efficiency} = \frac{\text{Liquefied Hydrogen LHV}}{\text{Liquefied Hydrogen LHV} + \text{Liquefaction Energy}}$$

- **Phase I - Feasibility**
 - Develop Novel Conceptual Process Designs
 - Validate Improved Ortho-Para Performance
- **Phase II - Process Development**
 - Establish Performance Targets
 - Develop Preliminary Capital Cost Estimate
- **Phase III – Performance Evaluation**
 - Demonstrate Ortho-Para Performance
 - Validate Capital Cost and Performance Improvement

Program Approach



- **Build on successful high-risk, low-effort program funded through EMTEC**
 - \$200,000 program that demonstrated potential for improved ortho-para conversion process
 - Enabled Praxair to propose this project to advance hydrogen liquefaction process development

- **Incorporate other process improvements beyond improved ortho-para conversion**

Phase I Plan



- **Process Optimization, Design, and Economics (45%)**
 - Develop alternative hydrogen liquefaction processes that can optimally integrate new equipment and improved ortho-para process

- **Process Equipment Evaluation (30%)**
 - Evaluate commercially available critical equipment
 - Evaluate novel turbomachinery

- **Ortho-Para Conversion Optimization (25%)**
 - Validate process performance in laboratory-scale test facilities

Liquid Hydrogen

- **In the 1960's, liquid hydrogen plants were built to support the Apollo program**

- Space shuttle capacity is 113 tons (383,000 gallons)
- Saturn V rocket used 100 tons (339,000 gallons)




Photo courtesy of NASA

- **Today, liquid hydrogen is used to reduce the cost of hydrogen distribution**


- Liquid hydrogen can be transported economically in larger quantities for longer distances than compressed gas
- Liquid hydrogen is used to provide high purity product because impurities condense before hydrogen

Hydrogen Liquefaction Existing Process Flow Diagram



Hydrogen Liquefaction

- **The plants are very capital intensive**
 - Infrequent builds make it difficult to reproduce designs
 - Large plants have high capital risk
 - Want to avoid unused capacity
- **The process is very energy intensive**
 - Typical unit powers are about 12.5 to 15 kWh_e/kg
 - Hydrogen lower heating value is about 33 kWh/kg
 - Hydrogen boiling point is 20 K = - 253°C = - 423°F
- **Capital cost is more than half of the total**



Hydrogen Distribution



Liquid Tanker
4500 kg H₂



Tube Trailer
300 kg H₂

- **Both weigh about 80,000 lbs**
- **Liquid hydrogen might not be the best way to supply the “Hydrogen Economy”, but it will play a significant role in the transition period**

Hydrogen Delivery




- **Pipeline (~ 1 billion scfd)**
 - Refineries and other large hydrogen consumers


- **Liquid (~ 10 million scfd)**
 - 1.8 million scf/truck
 - Liquid serves an important market segment

- **Tube Trailers**
 - 125,000 scf/truck

- **Cylinders**
 - 250 scf/cylinder



Forms of Molecular Hydrogen




- **Difference is due to proton spin**
 - Normal Hydrogen is 75% Ortho, 25% Para
 - Equilibrium Liquid Hydrogen is 0.2% Ortho, 99.8% Para

- **Ortho-Para conversion requires 18 - 45% of the minimum work requirement for liquefaction***
 - Depends on the conversion process used


* From Baker, C. R. and Shaner, R. L. *A Study of the Efficiency of Hydrogen Liquefaction*, Int. J. Hydrogen Energy, v. 3, p. 321, 1978.

Equilibrium Composition



- **Para fraction increases as temperature approaches liquid range**
 - Catalyst is used to reach equilibrium composition during cooling


Ortho-Para Enthalpy



- Heat of liquefaction/vaporization is 192 Btu/lb
- Heat of conversion from n-H₂ to e-H₂ in liquid is higher

From Singleton, A. H. and Lapin, A. *Design of Para-Orthohydrogen Catalytic Reactors*, Adv. Cryo. Eng., v. 11, p. 617, 1965.

Boil-Off Loss



- **Heat of conversion from normal to para is higher than the heat of liquefaction**
 - Spontaneous conversion in the storage tank can cause vaporization

Calculated values from:

Gursu, S. et al. *An Optimization Study of Liquid Hydrogen Boil-Off Losses*, Int. J. Hydrogen Energy., v. 17, p. 227, 1992.

Future Work – Task 1



- **Process Optimization, Design, and Economics**
 - Develop alternative liquefaction processes
 - 2009 Critical Milestone
 - Incorporate improved ortho-para conversion process
 - Estimate capital cost
 - 2010 Critical Milestone
 - Establish component performance targets
 - 2010 Critical Milestone
 - Develop process simulations for new designs
 - Validate potential cost reduction
 - 2011 Critical Milestone

Future Work – Task 2



- **Process Equipment Evaluation**
 - Evaluate commercially available critical equipment
 - Use this to develop new liquefaction processes
 - Evaluate novel turbomachinery
 - Use this to develop new liquefaction processes
 - Estimate capital cost
 - 2010 Critical Milestone
 - Update critical equipment evaluation

Equipment development is beyond the scope of this program

Future Work – Task 3



- **Ortho-Para Conversion Process Optimization**
 - Validate improved ortho-para performance
 - 2009 Critical Milestone
 - Select best candidate ortho-para process
 - Demonstrate process performance
 - 2011 Critical Milestone

Hydrogen Liquefier Equipment Design Considerations



| Component | State of the Art | Near Term | Long Term |
|---------------------------|-------------------------|---|-------------------------------------|
| Compressors | Reciprocating Screw | Reciprocating Centrifugal | Centrifugal Hydride Shockwave |
| Pre-Cooling | Liquid N ₂ | Mixed gas | Magnetic |
| Low-Temp Refrigeration | Reverse Brayton | Reverse Brayton with advanced turbines | Magnetic Acoustic |
| Heat Exchangers | Brazed aluminum | Brazed aluminum Micro-channel | Micro-channel |
| Ortho-Para Conversion | Catalytic conversion | Improved ortho-para process | Advanced ortho-para process |

Summary

- **Multi-faceted approach to improving hydrogen liquefaction by improving process efficiency and reducing capital cost**
- **Goal is to define a new liquefaction process that integrates state-of-the-art equipment and takes full advantage of its increased capability**
- **Incorporate improved ortho-para conversion process already under development**