

Innovation for Our Energy Future

### Technology Validation: Fuel Cell Bus Evaluations

Leslie Eudy, Sr. Project Leader NREL June 9, 2008

Presented at the 2008 DOE Hydrogen, Fuel Cells & Infrastructure Technologies Program Review, Washington, DC

> Project ID# TVP2

This presentation does not contain any proprietary, confidential, or otherwise restricted information



### **Overview**

<ul> <li>First generation FCB complete in FY08</li> <li>Second generation FCBs begin 2<sup>nd</sup> Qtr 2008</li> </ul>	<ul> <li>Barriers</li> <li>A. Lack of fuel cell vehicle performance and durability data</li> <li>B. Lack of H<sub>2</sub> fueling infrastructure performance and availability data</li> <li>D. Maintenance and training facilities</li> </ul>
<ul> <li>Budget</li> <li>FY 2008: \$288K</li> <li>FY 2007: \$288K</li> <li>FY 2006: \$288K</li> </ul>	<ul> <li>Partners</li> <li>Fleets: Operational data, fleet experience</li> <li>Manufacturers: Vehicle specs, data and review</li> <li>Fuel Providers: Fueling data and review</li> </ul>

# **Objectives**

- Overall: Validate fuel cell and hydrogen technologies in transit applications
  - Show progress of the technology toward commercialization
  - Provide "lessons learned" on implementing next generation fuel cell systems in transit operations
  - Harmonize data collection efforts with other fuel cell bus demonstrations worldwide (in coordination with FTA and other U.S. and international partners)
- 2008
  - Complete update reports AC Transit and SunLine
  - Begin data collection and analysis for first cold climate site:
     CTTRANSIT
  - Summary of FCB experience and analysis of status



### Milestones

- Begin data collection on cold climate sites – Hartford, CT: FY07
- Complete evaluations of 1<sup>st</sup> generation FCBs:
  - Santa Clara VTA: completed FY07
  - AC Transit: FY08
  - SunLine: FY08
  - CTTRANSIT: FY09
- Begin evaluations of 2<sup>nd</sup> generation FCBs 2<sup>nd</sup> Qtr: FY08

### **Evaluation Approach**

### Two levels of data collected

- Non-sensitive data
  - Follows existing protocol
  - Data collected mainly from fleet
  - Results are made public after project team review

Effect Test <u>A Praduation</u> Verschwarze Brank undersch 19 Indersch Brank undersch 1										
General Evalu Fleet Test & Evalua		Table 1. Data Collection Items								
A CONTRACTOR OF	Type of Data	Frequency Recorded	Data Items							
	Vehicle Specification and Performance Expectations									
	Vehicle System Descriptions	Start of data collection and changes as needed	Data items shown in Appendix C							
Mailine for Street	Vehicle Performance Expectations	Start of data collection and changes as needed	Criteria and testing results for performance expectations							
	Vehicle Operation									
	Vehicle Operating Cycle	Start of data collection and changes as needed	General description of daily use of vehicles							
	Special Service (Press events, public education, etc.)	Each time vehicle is used for atypical service	Description of event, time out of service.							
	Vehicle Usage in Service	At each time usage is measured	Odometer reading; hours of vehicle and fuel cell operation							
			Daily vehicle assignment							
			GPS data (if needed)							
	Fuel Consumption	Each time a vehicle is fueled	Amount of fuel							

- Proprietary data
  - Collected from manufacturer
  - Protected in Secure Data Center at NREL
  - Only aggregate data products made public

					ACCON-Road	and the second sec	0 με (χναρν ()	De Perfo	ormance
iat yew part fyrest ) al 2, 3, 4, 5, 5, 5, 5, 5, al 3, 5, 6, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,	nA Parameters Template (New A) ols goah (gata gyndaw yelp add a 2 → Σ → (ga 100% → Higg (ga 10% Rack) with Charges	ge FOF Arial 10	- B Z I E E E I I S	9	other formation information Date of Vehicle Operating Loca Fleet Site	tion	at, *.mdf, etc, early identified Date insert operating k insert fleet name	) may be a ed in the d	cceptable
A B C A B C A A B C A A A B A A A A A A		~		13 14 15 16	FC System Inte Vehicle Number All the above da For ease of reco	Bus Chassis Manufacturer interf but manufacturer PE Manufacturer interf but manufacturer PEC Stytem Integrator (ff differer integrator PEC manufacturer Vehicle Number * All fina above data Fridda need not 6 intoladar in each data data fridda need not 6 intoladar in each data data fridda need not 6 intoladar inter data data fridda need not 6 intoladar inter data data fridda need not 6 intoladar inter data data fridda need not 6 intoladar interdata All fina dove data Fridda need not 6 intoladar interdata data data data data fridda need not 6 intoladar interdata data data data data data data data			
ating Location	insert location insert fireit	-	Yellow cell indicates data already	16	Company	N/A		Vehic	
Chassis Manufacturer Ianufacturer	insert bus manufacturer insert FC manufacturer insert system integrator		These data are considered non- as part of future Fleet Evaluation		Measurement	Тлю	Vehicle Speed	Cumulative Operating Hours	Start/St
ude parameters fo	r each vehicle and p	ower plant	Vehicle, Power Plant Configuration			Seconds (at			t = on (fron start-up sequ
		Vehicle Model	insert vehicle model	21	Units	least 1 data point per second)	Mieshour	Hours	(trom begin down s
		Power Plant Model		22			111111111	1.00 00 10	
Parameter	Units	Comments	Value	28			_	-	
CD	dimensionless	Coefficient of drag		35					-
FA	m2	Frontal area				story ) On-Road Da			
cle Mass a. Front Axel	kg kg	Curb weight		Dga	w = id Agethope	-1100		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	1 * III    II

### Evaluation of Hydrogen and Fuel Cell Buses in Five Fleets

Santa Clara VTA, San Jose, CA - completed Ballard, Gillig: non-hybrid FCB SunLine, Thousand Palms, CA UTC Power, ISE Corp: hybrid FCB ISE Corp: hybrid H<sub>2</sub> ICE AC Transit, Oakland, CA UTC Power, ISE Corp: hybrid FCB **CTTRANSIT**, Hartford, CT UTC Power, ISE Corp: hybrid FCB Hickam AFB, Honolulu, HI Hydrogenics, Enova: hybrid system




ZERO EMISSIONS FUEL CE

### Comparison of Hydrogen and Fuel Cell Buses to Conventional Technology

# Targets for assessing the progress toward commercialization

- Performance characteristics
- Bus use
- Fuel economy
- Availability
- Reliability miles between road call (MBRC)
- Cost capital, fueling, and maintenance



### Fleet Data Summary: AC Transit

#### Fuel Cell Bus (hybrid system)





- 24 months operation of 3 FCBs
- Total miles: 82,066
- Total FC system hours: 7,814



- 24 months operation of 6 diesel buses
- Total miles: 459,096








# Fleet Data Summary: AC Transit

### **Summary of Costs**



NREL National Renewable Energy Lab

Alameda-Contra Costa Transit Distr (AC Transit) Fuel Cell Transit Buses: Evaluation Results Update

Kevin Chandler, Battelle Leslie Eudy, National Renewable



\* Warranty data is not included in calculations. Manufacturer staff are conducting most of the system repairs. Costs are expected to increase as fleet takes over these tasks.


#### Update Report Published 9/07 Available online at www.nrel.gov/hydrogen/pdfs/42249.pdf

### **Evaluation Status**

- Complete for current generation buses
- Final data report planned for spring
- Data collection will continue under FTA funding (Accelerated testing of current generation)
- Next generation buses arrive 2009 (planned DOE evaluation)




# Fleet Data Summary: SunLine



# Fleet Data Summary: SunLine

### Summary of Costs\*



### **Evaluation Status**

- Data collection on current gen design nearly complete – final report in summer
- Begin data collection on bus with new design FC



\* Warranty data is not included in calculations. Manufacturer staff are conducting most of the system repairs. Costs are expected to increase as fleet takes over these tasks.

> Update report published 9/07 Available online at www.nrel.gov/hydrogen/pdfs/42080.pdf

# Fleet Data Summary: CTTRANSIT


#### Fuel Cell Bus (hybrid system)



- 12 months operation of 1 FCB
- Total miles: 9,298
- Total FC system hours: 1,596




- 8 months operation of 3 diesel buses
- Total miles: 70,236



# Fleet Data Summary: CTTRANSIT

#### Summary of Costs\*



### **Evaluation Status**

- In-Progress
- 1<sup>st</sup> fleet operating in cold climate
- First data report summer 2008

RANSIT Operates New England's st Fuel Cell Hybrid Bus



13

\* Warranty data is not included in calculations. Manufacturer staff are conducting most of the system repairs with assistance from agency staff. Costs are expected to increase as fleet takes over these tasks.

> Fact Sheet Published 2/08 Available online at www.nrel.gov/hydrogen/pdfs/42407.pdf



# **Infrastructure Data Summary**

#### VTA


- Air Products
- Liquid H<sub>2</sub> storage
- Dispenses compressed H<sub>2</sub>
- 32 months data

#### SunLine

- HyRadix
- Natural gas reformer
- 13 months data


#### **AC Transit**

- Chevron
- Natural gas reformer
- 24 months data CTTRANSIT
- UTC Power station
- Praxair
- Liquid H<sub>2</sub> storage
- Dispenses compressed H<sub>2</sub>
- 9 months data



### **Infrastructure Data Summary**





### **Future Work**

- Remainder of FY 2008
  - Complete data analysis reports on AC Transit and SunLine
  - Initiate data collection on SunLine FCB with next generation fuel cell power system
  - Complete first data analysis report on CTTRANSIT
  - Complete update to FCB Summary and Status paper
- FY 2009
  - Complete analysis and final data report on Hickam
  - Complete update data analysis and report on CTTRANSIT and SunLine
  - Initiate data collection for second generation design FCBs at AC Transit and VTA
  - Coordinate data collection activities with FTA

### Planned FCB Evaluations for DOE and FTA

Site/Locations	State	Eval.	20	07	2008				2009				2010			
	Sidle	Funding	3	4	1	2	3	4	1	2	3	4	1	2	3	4
AC Transit /Oakland	CA		HyR	load												
AC Transit /Oakland	CA	uo								A	NC Tra	ansit (	CA ZE	B 200	)9	
SunLine /Thousand Palms	CA	lati	FC	B/HH	ICE											
SunLine /Thousand Palms	CA	DOE Validation			FC	B Ext	. Serv	vice								
SunLine /Thousand Palms	CA									Ad	vance	ed FC	B Pro	ject		
CTTRANSIT /Hartford	СТ	_ech.		(	CTTR	ANSIT	<b>FCB</b>	Dem	0							
Hickam AFB /Honolulu	HI	Te		Air F	orce	FCV [	Demo									
VTA /San Jose	CA										VT	A CA	ZEB 2	2009		
AC Transit /Oakland	CA	<u>ہ</u> *		Α	ccele	rated	Testii	ng								
SunLine /Thousand Palms	CA	Fuel am*								Α	neric	an FC	B De	mo		
CTTRANSIT /Hartford	СТ	al F ogrå								C	l Hyb	rid FC	B De	mo		
Columbia /Site 2/ CTTRANSIT	SC/CT	National Fuel us Program*							Dual	Varia	ble O	utput	Hybri	d FCE	3	
Logan Airport /Boston	MA	Nati Bus I	Nati	onal								MA	<b>h</b> H2 F	CB F	leet	
NFTA /Buffalo	NY	<u>— ш</u>	Fu	el Ce	ll Bu	l Bus			Lightweight FCB Demo							
NFTA /Buffalo	NY	FTA Cell	Program			Ну					Hydroelectric H2 Powered FCB					
SFMTA /San Francisco	CA													FC A	PUH	ybrid

Demonstration sites are color coded by area:

California New England Western NY Southeast Hawaii South \* Detailed data analysis funded by DOE

### Summary

- Collected operational, performance, and cost data on 9 hydrogen fueled buses in real-world service at four transit agencies:
  - VTA: 17 months
  - SunLine: 27 months
  - AC Transit: 24 months
  - CTTRANSIT: 12 months
- Validated fuel cell bus performance characteristics equal to or better than diesel
  - Drivers report better acceleration and quiet operation
- Demonstrated that bus duty-cycle allows fast accumulation of miles/FC hours
  - Over 220,000 total miles and over 16,000 FC hours
- Collected performance and cost data on conventional technology to establish a baseline for tracking progress
  - Use of prototype FCBs is increasing, but still much less than standard buses
  - High cost for maintaining current generation prototype technology
- Transit agency staff are being trained to handle more of the maintenance repairs
  - For early demonstrations, all propulsion system related maintenance was handled by on-site manufacturer staff
  - Expect costs to rise



# **Summary (continued)**

- Fuel cell bus use less than baseline
  - Beginning to increase as fleets accelerate testing
- Fuel economy
  - Highly dependent on duty-cycle
  - Results show need for hybridization
  - Improvement over conventional technology approaching 2X

