



Advanced Hydrogen Liquefaction Process

Contract Number: DE-FG36-08GO18063

Jerry Jankowiak
Joe Schwartz
Praxair - Tonawanda, NY

DOE Annual Merit Review Meeting
May 21, 2009

Copyright © 2009 Praxair Technology, Inc.

This paper was written with support of the U.S. Department of Energy under Contract No. DE-FG36-08GO18063. The Government reserves for itself and others acting on its behalf a royalty-free, nonexclusive, irrevocable, worldwide license for Governmental purposes to publish, distribute, translate, duplicate, exhibit, and perform this copyrighted paper. This presentation does not contain any proprietary, confidential, or otherwise restricted information.




Project ID
PD_36_Jankowiak

Overview



Program Timeline

7/08 – 12/09 1/10 – 12/10 1/11-12/11



Phase I Budget

	Total	Spent (as of March 15)
DOE	500,000	63,222
Praxair	125,000	15,805
TOTAL	625,000	79,027

13% Complete

- **Phase I – Feasibility**
 - 1 Develop Alternative Hydrogen Liquefaction Processes
 - 2 Validate Ortho-Para Conversion Process Performance
- **Phase II – Hydrogen Liquefaction Process Development**
 - 3 Establish Efficiency, Equipment, and Material Performance Targets
 - 4 Estimate Capital Cost
- **Phase III – Process Performance Evaluation**
 - 5 Demonstrate Improved Ortho-Para Conversion Process
 - 6 Evaluate Potential Cost Reduction and Efficiency Improvement


Barriers Addressed

- **C. High Cost and Low Energy Efficiency of Hydrogen Liquefaction**
 - Reduced capital cost
 - Improved efficiency
 - Improved overall process by integration

Hydrogen Delivery - Relevance



- **Pipeline (~ 1 billion scfd)**
 - Refineries and other large hydrogen consumers
- **Liquid (~ 10 million scfd)**
 - 1.8 million scf/truck
 - Liquefaction is energy intensive and expensive
 - Liquid serves an important market segment
- **Tube Trailers**
 - 125,000 scf/truck
- **Cylinders**
 - 250 scf/cylinder



DOE Targets – Relevance



Category	2005 Status	2012	2017
<i>Small-Scale Liquefaction (30,000 kg H₂/day)</i>			
Installed Capital Cost (\$)	\$50M	\$40M	\$30M
Energy Efficiency (%)	70%	75%	85%
<i>Large-Scale Liquefaction (300,000 kg H₂/day)</i>			
Installed Capital Cost (\$)	\$170M	\$130M	\$100M
Energy Efficiency (%)	80%	>80%	87%


$$\text{Efficiency} = \frac{\text{Liquefied Hydrogen LHV}}{\text{Liquefied Hydrogen LHV} + \text{Liquefaction Energy}}$$

Objectives - Relevance




- **Program - Develop a low-cost hydrogen liquefaction system for 30 and 300 tons/day that meets or exceeds DOE targets for 2012**
 - Improve liquefaction energy efficiency
 - Reduce liquefier capital cost
 - Integrate improved process equipment invented since last liquefier was designed
 - Continue ortho-para conversion process development
 - Integrate improved ortho-para conversion process
 - Develop optimized new liquefaction process based on new equipment and new ortho-para conversion process
- **Phase I – Feasibility**
 - Develop conceptual designs for improved processes
 - Validate ortho-para conversion process performance

Hydrogen Liquefaction Existing Process Flow Diagram




Forms of Molecular Hydrogen

Ortho




Para



- **Difference is due to proton spin**
 - Normal Hydrogen is 75% Ortho, 25% Para
 - Equilibrium Liquid Hydrogen is 0.2% Ortho, 99.8% Para
- **Ortho-Para conversion requires 18 - 45% of the minimum work requirement for liquefaction***
 - Depends on the conversion process used
 - No sensible heat removed


* From Baker, C. R. and Shaner, R. L. *A Study of the Efficiency of Hydrogen Liquefaction*, Int. J. Hydrogen Energy, v. 3, p. 321, 1978.

Equilibrium Composition



- **Para fraction increases as temperature approaches liquid range**
 - Catalyst is used to reach equilibrium composition during cooling

Why It Matters - Boil-Off Loss



- **Heat of conversion from normal to para is higher than the heat of liquefaction**
 - Spontaneous conversion in the storage tank can cause vaporization

Calculated values from:

Gursu, S. et al. *An Optimization Study of Liquid Hydrogen Boil-Off Losses*, Int. J. Hydrogen Energy., v. 17, p. 227, 1992.

Program Approach

- **Build on successful high-risk, low-effort program funded through EMTEC**
 - \$200,000 program that demonstrated potential for improved ortho-para conversion process
 - Enabled Praxair to propose this project to advance hydrogen liquefaction process development

- **Expand program to incorporate other process improvements beyond improved ortho-para conversion to increase efficiency and reduce cost**
 - Design a process with higher efficiency
 - Implement improved process equipment
 - Optimize improved ortho-para conversion process

Milestones - Approach



- **Phase I - Feasibility**
 - Develop Novel Conceptual Process Designs
 - Validate Improved Ortho-Para Performance
- **Phase II - Process Development**
 - Establish Performance Targets
 - Develop Preliminary Capital Cost Estimate
- **Phase III – Performance Evaluation**
 - Demonstrate Ortho-Para Performance
 - Validate Capital Cost and Performance Improvement

Phase I Plan - Approach

- **Process Optimization, Design, and Economics (45%)**
 - Develop alternative hydrogen liquefaction processes that can optimally integrate new equipment and improved ortho-para process

- **Process Equipment Evaluation (30%)**
 - Evaluate commercially available critical equipment
 - Evaluate novel turbomachinery

- **Ortho-Para Conversion Optimization (25%)**
 - Validate process performance in laboratory-scale test facilities

Thermodynamic Model - Progress



- **Typical models are not accurate near the critical point**
 - Need to handle temps from 20K to 300K. Critical point is at 33K which is near where the liquefaction occurs.
- **Typical models do not distinguish between ortho and para**
 - Cannot predict heat of conversion from ortho to para
 - Need to predict this accurately in order to maximize energy savings around this step of the process.
- **New model developed by Leachman *et al.* handles these issues**
 - Accurate equations of state for both ortho and para hydrogen.

Leachman, J. W. et al., *Fundamental Equations of State for Parahydrogen, Normal Hydrogen and Orthohydrogen*, Journal of Physical and Chemical Reference Data, (In Review).

Thermodynamic Model - Progress



- **Written in terms of the Helmholtz free energy along with an expression for the ideal gas heat capacity**
 - All other thermodynamic properties can be determined from this equation
- **Our new process modeling software does not include these equations of state**
- **Next step is to program a thermo “socket” that works with our new process modeling software to implement these equations**
- **NIST provides a software package that generates thermodynamic data from equations of state and implements the Leachman equations**
 - This will be used to check our thermo socket and to validate any data that comes from the process model.

Process Models - Progress



- **Both traditional and advanced liquefaction processes are being modeled**
 - Both models will be thoroughly examined to pinpoint areas where energy and cost savings can be achieved
 - Experimental results will be used to model ortho-para conversion performance
 - The model will also be used to propose new experiments when better operating conditions are discovered

Ortho-Para Conversion - Progress

- Large and small test systems have been constructed
- Safety reviews completed
- Liquid nitrogen used for cooling
- Testing scheduled to begin in 2Q09



Future Work – Task 1

- **Process Optimization, Design, and Economics**
 - Develop alternative liquefaction processes
 - 2009 Critical Milestone
 - Incorporate improved ortho-para conversion process
 - Estimate capital cost
 - 2010 Critical Milestone
 - Establish component performance targets
 - 2010 Critical Milestone
 - Validate potential cost reduction
 - 2011 Critical Milestone

Future Work – Task 2



- **Process Equipment Evaluation**
 - Evaluate commercially available critical equipment
 - Use this to develop new liquefaction processes
 - Evaluate novel turbomachinery
 - Use this to develop new liquefaction processes
 - Estimate capital cost
 - 2010 Critical Milestone
 - Update critical equipment evaluation

Equipment development is beyond the scope of this program

Future Work – Task 3



- **Ortho-Para Conversion Process Optimization**
 - Validate improved ortho-para performance
 - 2009 Critical Milestone
 - Select best candidate ortho-para process
 - Demonstrate process performance
 - 2011 Critical Milestone

Summary

- **Multi-faceted approach to improving hydrogen liquefaction by improving process efficiency and reducing capital cost**
- **Goal is to define a new liquefaction process that integrates improved ortho-para conversion with state-of-the-art equipment and takes full advantage of its increased capability**
- **Program is in the initial part of Phase I**