


D.O.E. Program Review

Modular, High-Volume Fuel Cell Leak-Test Suite and Process



UltraCell。

Ian Kaye, Ru Chen, Matt Mendez **UltraCell Corporation**

Peter Rieke, Dale King Pacific Northwest National Laboratory

Gordon Splete Cincinnati Test Systems

June 11, 2010

Project ID # MN003

This presentation does not contain any proprietary, confidential, or otherwise restricted information

Overview



Timeline

- Start: 09/01/2008
- End: 08/31/2011
- 50% complete

Budget

- Total project funding
 - DOE \$2,411,888
 - Contractor \$2,281,603
- Funding received in FY09
 - \$1,041,805
- Funding for FY10
 - \$253,013

The funding shown for FY09 and FY10 are actual expenditures rather than DOE obligations

Barriers

F: Low levels of Quality Control and inflexible processes

Partners

- UltraCell Project lead
- PNNL Fuel cell stack properties, method selection, quality metrics
- CTS Leak-test suite design, fabrication, and installation




Objectives - Relevance

- A fuel cell is an excellent leak-sensor: we use the manufactured part as part of the sensor network
- Project Objectives
 - Design a modular, high-volume fuel cell leak-test suite capable of testing in excess of 100,000 fuel cell stack per year (i.e., 50 fuel cell stacks per hour).
 - Perform leak tests inline during assembly and break-in steps
 - Demonstrate fuel cell stack yield rate to 95%.
 - Reduce labor content to 6 min.
 - Reduce fuel cell stack manufacturing cost by 80%.

Objectives for past year

- Develop leak-test methods
- Design and fabricate leak-test suite prototype

Milestones - Relevance






U.S. DEPARTMENT OF

Pacific Northwest







UltraCell.




Features

- ✓ Automation
- ✓ Inline leak-test during stack manufacturing
- Multi-functions: combined leak tests, compression, break-in and power performance in one system
- ✓ Diagnostics
- ✓ Safety feature






Pressure Decay Test





Crossover Current Test



LEADING A REVOLUTION IN MOBILE POWER™

OCV Decay Test





C

U.S. DEPARTMENT OF

• Milestones (FY10)

- 11/08 Manufacturing process analysis
- 07/09 Demonstrate leak check accuracy
- 07/09 Go/No-Go: Flexo-Tiltometer accuracy
- 11/09 Complete design review package
- 12/10 Achieve 5 pph capacity on prototype leak test suite
- 12/10 Go/No-Go: design of 50 pph leak test suite

Progress


- Analyzed fuel cell stack manufacturing process procedure, throughput time, labor time, yield, failure modes
- Investigated leak-test methods
- Investigated fuel cell stack components
- Designed and fabricated leak-test suite lab prototype
- Validated leak-test suite lab prototype



Technical Accomplishments

The leak-test suite lab prototype is a combination of the following main areas:

Machine Control
Fuel Cell Test Chamber
Hydraulic Press with Pump
Pneumatic Tooling
Pneumatic Test Circuits
Flexo-tiltometer
Measurement
Electrical Measurement
Gas Exhaust System





U.S. DEPARTMENT C

Pacific Northwes


Technical Accomplishments




Main




Control



Setup




Test



LEADING A REVOLUTION IN MOBILE POWER™

Mechanical Analysis of Stack Materials



REVOLUTION IN MOBILE POWER™

Static Compression. Relevant to initial stack compression

> Creep & Recovery. Relevant to slow changes in stack structure

Dynamic Mechanical Analysis vs. Temperature. Differentiation of materials based upon glass transition temperature.


1) Variety of mechanical analysis techniques

U.S. DEPARTMENT OF

Pacific Northwes


- 2) Data base of individual properties
- Used in modeling mechanics of assembled stack

3 mm probe tip allows high local pressures with minimal force but is not useful for assemblies



Modeling Stack Mechanical Properties


S. DEPARTMENT O



UITTACCEII® Leading a revolution in mobile power™


Comparison of Automated and Manual Testing

(with a specific stack)



Stack developed an external leak at temperature which seal upon cooling


UITTACEII.



As documented in the manual test Cell 9 failed under load with reformate fuel. All others passed.

- 1) Significant reduction in testing time
- 2) Increase in test reproducibility
- 3) Time dependent data acquired
- 4) More tests performed
- 5) Leak test performed at high temperatures

Collaborations



Project lead. Leading producer of fuel cell

UltraCell Corporation

systems for remote or mobile devices

U.S. DEPARTMENT OF

Pacific Northwest

Pacific Northwest National Laboratory

> Stack properties, method selection, quality metrics

- **Cincinnati Test Systems** Leak-test suite design, fabrication, and installation
- Invotec Engineering, Inc. Design, fabrication, and installation of fuel cell stack robotic manufacturing system
- Mound Technical Solutions, Inc.

Design and fabrication of fuel cell performance test fixture and automated test data analysis



Future Work

- Fabricate, integrate, test and evaluate leak-test suite
- Modify pilot production line to accommodate leak test suite
- Test run pilot production line with leak-test suite
- Validate leak-test suite



Pacific Northwest

Summary



Objectives

- Design a modular, high-volume fuel cell leak-test suite capable of testing in excess of 100,000 fuel cell stack per year (i.e., 50 fuel cell stacks per hour).
- Perform leak tests inline during assembly and break-in steps

Progress

- Analyzed fuel cell stack manufacturing process
- Investigated leak-test methods
- Investigated fuel cell stack components
- Designed, fabricated, and tested leak-test suite lab prototype

Future Work

- Fabricate, integrate, test and evaluate leak-test suite
- Test run pilot production line with leak-test suite

