



# Advanced Materials for RSOFC Dual Mode Operation with Low Degradation

Eric Tang, Mark Richards, and Randy Petri (PI)  
Versa Power Systems Inc.  
2011 DOE Hydrogen Program Review  
May 12, 2011  
Washington, DC

Project ID: FC042

## Overview

---

### ▶ Timeline

- Start: September 2009
- End: August 2011
- 80% complete (ahead of schedule)

### ▶ Budget

- \$1,994,618 total project
  - \$1,595,694 DOE share
  - \$398,924 VPS share
- \$76,857 in FY10
- \$518,837 in FY11


### ▶ Barriers

- A. Durability
- B. Cost
- C. Performance

### ▶ Partners


- Boeing
- Idaho National Laboratory (INL)

# Project Background




Relevance

- ▶ Reversible Solid Oxide Fuel Cells (RSOFCs) are energy conversion devices: they are capable of operating in both power generation mode (SOFC) and electrolysis mode (SOEC)
- ▶ RSOFC can integrate renewable production of electricity and hydrogen when power generation and steam electrolysis are coupled in a system, which can turn intermittent solar and wind energy into “firm power”



## Project Objectives

- ▶ To advance RSOFC stack technology in the areas of endurance and performance through RSOFC materials development and reversible stack design
- ▶ To meet the following performance targets in a kW-class RSOFC stack demonstration:
  - RSOFC dual mode operation of 1500 hours with more than ten SOFC/SOEC transitions
    - Performance (C), Durability (A)
  - Operating current density of more than 300 mA/cm<sup>2</sup> in both SOFC and SOEC modes
    - Cost (B), Performance (C)
  - Overall decay rate of less than 4% per 1000 hours of operation
    - Durability (A), Cost (B)




## How Objectives Address Barriers

Relevance

	Hurdle	Targets
Endurance	<p><b>Performance decay in SOEC mode is too high for RSOFC system development</b></p> <ul style="list-style-type: none"> <li>▶ Materials system is not stable at SOEC operating mode with a decay rate more than 20% per 1000 hours</li> <li>▶ Performance decay during transient between SOEC and SOFC is high</li> </ul>	<p><b>Reducing decay to under 4% per 1000 hours for both SOFC and SOEC</b></p> <ul style="list-style-type: none"> <li>▶ <b>Met endurance target in a 1000 hour single cell test (month 15)</b></li> <li>▶ Meet endurance target in a 1500 hours kW-class stack (month 24)</li> <li>▶ Demonstrate transient capability with more than 10 FC/EC transients</li> </ul>
Performance	<p><b>Performance in SOEC mode is not sufficient for viable RSOFC system development</b></p> <ul style="list-style-type: none"> <li>▶ ASR is more than 1.0 <math>\Omega\text{-cm}^2</math> at 750 C and below in SOEC mode</li> </ul>	<p><b>Improve performance at 750 C in SOEC mode by reducing ASR to less than 0.3 <math>\Omega\text{-cm}^2</math></b></p> <ul style="list-style-type: none"> <li>▶ <b>Met performance technical target in a single cell test (month 15)</b></li> <li>▶ Operate kW-class RSOFC stack at more than 300 mA/cm<sup>2</sup></li> </ul>

# Project Timeline, Milestones, Decision Points



## Decision Points and Milestones


---

- Approach**
- ★ In February 2011, the second budget period effort was approved based on 1000 hour single cell test relative to the following performance and endurance metrics:
    - RSOFC area specific resistance of less than  $0.3 \Omega\text{-cm}^2$  in both SOFC and SOEC operating modes
    - Operating current density of more than  $300 \text{mA/cm}^2$  in both SOFC and SOEC modes
    - Overall decay rate of less than 4% per 1000 hours of operation
  - ▶ Five technical milestones will be tracked and measured throughout the project
    - 1 Task 1: Completion of degradation mechanisms study of baseline cells (4<sup>th</sup> quarter)
    - 2 Task 2: Completion of RSOFC cell materials selection (6<sup>th</sup> quarter)
    - 3 Task 3: Completion of RSOFC interconnect materials selection (6<sup>th</sup> quarter)
    - 4 Task 4: Completion of RSOFC stack design (7<sup>th</sup> quarter)
    - 5 Task 4: Starting end of the project RSOFC stack metrics test (8<sup>th</sup> quarter)

# RSOFC Development Path


Approach

- ▶ Building on VPS' strong SOFC cell and stack baseline
- ▶ Leveraging cell and stack advancements from the DOE SECA SOFC project
- ▶ Addressing RSOFC degradation mechanisms in SOEC mode with innovative cell and stack repeat unit configurations
- ▶ Conducting parallel materials development activities and integrating them with cell production technology development
- ▶ Completing RSOFC stack and process designs to address durability, performance, and cost in both SOFC and SOEC operating modes





# RSOFC Cell Performance Development Status




**8 cell types passed the performance criteria of ASR less than 300 mΩ-cm<sup>2</sup> in both SOFC and SOEC modes at 750 C**

Cell Type	SOEC ASR (mΩ-cm <sup>2</sup> )	SOFC ASR (mΩ-cm <sup>2</sup> )
TSC-2	375	180
EC-1	366	281
EC-2	362	393
EC-3	278	251
RSOFC-1	308	245
RSOFC-1-MAC	251	245
RSOFC-2	285	295
RSOFC-3	386	283
RSOFC-4	268	238
RSOFC-5-MAC	341	253
RSOFC-6	271	242
RSOFC-7	223	224
RSOFC-8	194	223
RSOFC-9	230	219

- Fuel Cell (SOFC) ASR at 3% humidity and 750°C
- Electrolysis (SOEC) ASR at 50% humidity and 750°C

# RSOFC-7 Cell Performance


Technical Accomplishments and Progress



*High performance of RSOFC-7 can reduce hydrogen production cost in SOEC mode and improve efficiency in SOFC mode*

# RSOFC-7 Cell Performance at Ultra-High Electrolysis Current Density


Technical Accomplishments and Progress



*High performance of RSOFC-7 can reduce hydrogen production cost and meet DOE water electrolysis efficiency 2017 target of 75% at the same time*

# Electrolysis Degradation: Status

- ▶ 6 cell types have passed the degradation criteria of less than 4%/1000 hours in SOEC mode
- ▶ RSOFC-4 and RSOFC-7 passed both performance and degradation criteria




Cell Type	Electrolysis (SOEC) Degradation		
	mV / 1000 hrs	% / 1000 hrs	Duration (hrs)
Target	< 50	< 4	> 1000
TSC-2	91	7.3	2893
EC-1	27	2.2	8465
EC-2	~0	~0	2400
EC-3	72	5.8	1792
RSOFC-1	35	2.8	6472
RSOFC-2	120	9.6	1152
RSOFC-3	42	3.4	2653
RSOFC-4	24	1.9	3618
RSOFC-7	19	1.5	1005

- Post Test Analysis After 8000 Hours:**
- All electrochemical functional layers fully intact, no delamination between electrodes and electrolyte
  - No chemical impurities or contaminations, such as, Cr poisoning found in cathode (air electrode)
  - No microstructure coarsening found

# Steady-State Electrolysis Test of a RSOFC-7 Cell

## Degradation Curve

Glob 101780; (M1A2-1325), Oven #17, Oct. 29, 2010



***Demonstrated electrolysis mode degradation of ~1.5% per 1000 hours for the Go/No-Go Decision Test***


# Summary of Go/No-Go Decision Points

Technical Accomplishments and Progress

Metric	Target	Status
<input checked="" type="checkbox"/> <b>Performance</b> (Area specific resistance in both SOFC and SOEC operating modes)	<b>&lt; 0.3 <math>\Omega\text{-cm}^2</math></b>	<b>0.223 <math>\Omega\text{-cm}^2</math> in SOEC</b> <b>0.224 <math>\Omega\text{-cm}^2</math> in SOFC</b>
<input checked="" type="checkbox"/> <b>Degradation</b> (Overall decay rate)	<b>&lt; 4% per 1000 hours</b>	<b>~1.5% per 1000 hours</b>
<input checked="" type="checkbox"/> <b>Operating Duration</b>	<b>&gt; 1000 hours</b>	<b>1005 hours</b> (as of Go/No-Go Decision)
<input checked="" type="checkbox"/> <b>Operating Current Density</b>	<b>&gt; 300 mA/cm<sup>2</sup></b>	<b>500 mA/cm<sup>2</sup></b>

# Single Cell Electrolysis/Fuel Cell Cycling Test

GLOB 101659 - SOFC-SOEC Cycles TSC-2 Cell




**Demonstrated 100 electrolysis/fuel cell mode cycles**

# SOEC Stack Design and Development

Technical Accomplishments and Progress



## Design



## Development

- ▶ Developed fully integrated CFD model for RSOFC stack
- ▶ Excellent stack thermal profile at SOEC operating mode
- ▶ Investigated local current density and chemical species concentration in SOEC operating conditions
- ▶ Electrolysis kinetics yet to be verified and calibrated in stack testing


## Testing





# kW-Class Stack Testing for INL

GT056019-0150 TC1 Hold - 23/Jun/10  
28cell PCI- INL; Test Stand 1



## Collaborations

---

### ▶ Boeing

- Collaborated on and funded initial RSOFC development work through both Boeing and DARPA funded efforts
- DARPA Vulture Phase 2 project was started October 2011
  - RSOFC stack integration into full reversible system
  - Stack design and development for reduced cost and weight

### ▶ INL

- Eventual integration of SOEC technology for hydrogen production with Next Generation High Temperature Nuclear Reactor
- Demonstrated suitability of VPS SOEC technology for this application at the kW-class stack level

## Proposed Future Work

---

### ▶ FY2011

- Complete the final project metric test with a kW-class RSOFC stack
- Complete the additional cell development scope of advancing performance and degradation beyond the original project target

### ▶ *Potential Additional Scope for FY2011:*

- Complete RSOFC system economic study
- Explore the option of developing larger (up to 20 kW) stack for RSOFC operation
- Explore the option of developing a RSOFC system integrated with renewable energy sources, such as solar and wind

## Summary

<p><b>Relevance</b></p>	<ul style="list-style-type: none"> <li>▶ RSOFC can integrate renewable production of electricity and hydrogen when power generation and steam electrolysis are coupled in a system, which can turn intermittent solar and wind energy into “firm power”</li> </ul>
<p><b>Approach</b></p>	<ul style="list-style-type: none"> <li>▶ Developing high performance and low degradation RSOFC cell and stack technology is critical for the reversible SOFC/SOEC system</li> </ul>
<p><b>Technical Progress</b></p>	<ul style="list-style-type: none"> <li>▶ 11 types of RSOFC cells were developed in the project. Two types of cells (RSOFC-4 and RSOFC-7) exceeded both performance and degradation criteria</li> <li>▶ A steady-state single cell test of RSOFC-7 has run in electrolysis with a degradation rate of about 1.5% per 1000 hours</li> <li>▶ A baseline 28-cell stack (kW-class) test has run in electrolysis for over 1000 hours at about 1.3% per 1000 hours degradation rate</li> </ul>
<p><b>Collaboration</b></p>	<ul style="list-style-type: none"> <li>▶ Boeing/DARPA, SECA, and INL</li> </ul>
<p><b>Proposed Future Research</b></p>	<ul style="list-style-type: none"> <li>▶ In addition to executing the original project scope, additional development activities are under consideration to accelerate RSOFC technology development for integrating with renewable energy sources, such as solar and wind.</li> </ul>