

# Emergency Hydrogen Refueler for Individual Consumer Fuel Cell Vehicles

Daniel R. Carr and Michael C. Kimble  
Skyhaven Systems, LLC  
405 S. Lincoln Avenue, Suite B209  
Steamboat Springs, CO

June 14, 2018

DOE SBIR Phase I Contract DE-SC0017695

This presentation does not contain any proprietary, confidential, or otherwise restricted information

# Overview

---

## Timeline

- Project Start Date: June 12, 2017
- Project End Date: March 11, 2018
- Percent Complete: 100%

## Budget

- Total Project Budget: \$149,999
  - Contractor Share: \$0
  - Federal Share: \$149,999
- Funds Spent: \$149,999

## Barriers Addressed

- 100% Reaction Conversion of LiH to H<sub>2</sub>
- Passively Controlled H<sub>2</sub> Gas Evolution over 15 Minutes
- Reduced cost from \$391 to \$83

## Partners

- US DOE: Project Sponsor and Funding
- Skyhaven: Technical R&D
- Champlain College: Financial Modeling and Commercialization Planning

# Market Need

---

- A common concern for fuel cell vehicle operators is running out of hydrogen fuel
  - Sparse hydrogen filling stations
  - Operators can experience range anxiety
  - This lessens the appeal of these vehicles hindering their commercialization
- To overcome this shortfall, the DOE is interested in developing emergency hydrogen refuelers
  - Similar in concept to keeping a can of gas in the trunk
  - Compact and lightweight H<sub>2</sub> storage unit that can be stored in the vehicle trunk
  - Can be safely and reliably operated by the driver

# Value Proposition

---



- To meet this market need, a H<sub>2</sub> gas refueler is being developed
- Skyhaven's refueler product goals
  - Provides 0.75 kg (1.7 lb) of hydrogen fuel
  - Refills the vehicle within 15 minutes
  - Is activated with water giving it a long storage lifetime
  - Mass of 10 kg (22.8 lb) that includes the activating water
  - Compact space of 11 liters (0.4 ft<sup>3</sup>)
  - No moving parts helping to increase reliability
  - Material cost budget of \$391 in low production volumes
- With this product, the average fuel cell vehicle will have a 50 mile range enabling the operator to reach a hydrogen refueling station

# The Innovation

---


- Store lithium hydride powder in a hermetically sealed vessel
- When this chemical hydride is exposed to water vapor, it releases hydrogen gas instantaneously
  - $\text{LiH} + \text{H}_2\text{O} \rightarrow \text{H}_2 + \text{LiOH}$
- Use a network of water conduits placed throughout a packed bed of lithium hydride to shuttle liquid water
  - Liquid water pervaporates through the conduits introducing water vapor to the LiH particles
- Use hydrophilic micro-wick additives within the LiH to further disperse water to all LiH particles giving 100% reaction yield

# Water Activation of LiH to Release H<sub>2</sub> Gas: Vapor Versus Liquid Feed




- **Ideal scenario**

- React all LiH within 10-15 minutes
- Maintain bed temperature less than 100°C using water vapor feed
- Liquid water for bootstrapping




# Top Phase I Technical Challenges



- A : Maximizing the water vapor transport rate through the conduits
- B: Maximizing the distance that water vapor can transport into the LiH bed
- C: Overcoming LiOH films that hinder water transport to LiH particles
- D: Introducing liquid water into the conduits without pumps
- E: System engineering – start up, heat removal,  $H_2$  purity, reliability, refueler design, cost

# Technical Challenge A: Maximize the Water Vapor Rate Through the Conduits

- Fabricate water feed conduits that are dispersed throughout the LiH packed bed
- Choose conduit materials and design to minimize their size (and cost) while enabling water pervaporation through them





- Miniaturized tubular conduits produced operating at 80-100°C that maximize the water vapor transmission rate into the LiH bed



# Technical Challenge B&C: Maximize the Water Vapor Distance Through the LiH Bed


- Want water vapor to diffuse through long distances of LiH particles (and through LiOH films)
- This minimizes the number of water conduits and maximizes the amount of LiH
- Incorporate wick additives into LiH to shuttle water



- Increasing percentage of wick additives
  - Enables deeper water penetration into the LiH bed
  - Enables 100% LiH conversion in reasonable time periods (15 min)
  - However, compromises LiH content

# Technical Challenge D: Introducing Liquid Water into the Conduits




- Hydrogen refueler needs to use a gravity water-fed delivery system (no pumps)
- Challenge is getting liquid water to fill the miniaturized conduits quickly once activated



- Gravity fed operation shows similar behavior to pumping water through the conduits
- Room temperature gravity-fed water supply to a single cell achieved a reaction completion of 79%

# Technical Challenge E: Starting the H<sub>2</sub> Refueler

- User activates refueler via turning a valve that gravity feeds water to the conduits
- Want 80-100 °C internal refueler temperature quickly as possible
  - This significantly increases the water vapor transport rate
- Since direct liquid water-LiH contact immediately releases heat, consider using a limited number of direct liquid water-LiH conduits to bootstrap the reactor



# Technical Challenge E: Heat Removal

---


- Heat of reaction:

$$\Delta H_{Rxn} = \Delta H_{LiOH}^{\circ} + \Delta H_{H_2}^{\circ} - \Delta H_{LiH}^{\circ} - \Delta H_{H_2O}^{\circ}$$
$$\Delta H_{Rxn} = -155.3 \frac{kJ}{mol} LiH$$

- A refueler with 750 g of H<sub>2</sub> requires 2976 g LiH
- Total energy released: -58,134.6 kJ
- Assume refueler is designed to dispense H<sub>2</sub> over a 10 minute period
  - Total heat released is: -96.9 kW
- Heat release calculations show importance of a controlled water delivery system to minimize heat generation and subsequent heat removal requirements
- Use internal heat transfer fins coupled to external fins for cooling



# Technical Challenge E: H<sub>2</sub> Purity

- SAE J2719 – Hydrogen Fuel Quality Specification
  - Hydrogen lower limit of 99.97%
  - Water upper limit of 5 ppm
- Refueler will require a bed of silica gel to get below water threshold
- Gas chromatography has shown that no other by-products are produced from the reactor
  - Oxygen and nitrogen presence from fitting leak



# Technical Challenge E: Refueler Material Reliability




- Examined material compatibility of LiH, conduits, and wick additives
  - Determine if material interactions degrade the refueler in storage
- 12 reactors initially fabricated with 0.9 grams of LiH containing conduits and wick additives
- 2 reactors activated each month measuring the H<sub>2</sub> flow rate



- Reliability studies have shown that there are no material compatibility issues with the refueler
- H<sub>2</sub> is generated after months of storage proving LiH is maintaining its reactivity during storage
- Differences in performance are attributed to LiH/wick additive packaging



# Technical Challenge E: Refueler Design

- Repeatable units forming individual compartments
  - e.g., compartments comprised of five water delivery conduits with a single direct water feed conduit in the middle to bootstrap
- Compartment walls serve as the internal heat exchanger fins
- External fins for ambient convection thermal management



# Technical Challenge E: Refueler Design Shows Scalability

- Single conduit, 1.5" long
- 0.9 g LiH
- 7.3 ml H<sub>2</sub>/min/in conduit



- 4 conduits, 6.0" long
- 3.0 g LiH
- 11.7 ml H<sub>2</sub>/min/in conduit



# Technical Challenge E: Refueler Design for a H<sub>2</sub> Fueling Nozzle

- Approach
  - Injection plastic molded nozzle
  - One-time use device
  - Mimic nozzle design from refueler stations
  - 5' plastic hose from refueler to nozzle
- Phase II design effort



# Technical Challenge E: Reducing the Material Cost Less than \$391

Component	Phase I Pricing				Phase I H <sub>2</sub>		Phase II Expected H <sub>2</sub>		
	Bulk Price	Qty	Unit Pricing		Refueler Material Cost		Refueler Material Cost		
			Price	Unit	Qty	Cost	Qty	Unit Price	Cost
HX Fins	\$77.25	12" x 1000'	\$0.00054	in <sup>2</sup>	1764	\$0.95	1764	\$0.00054	\$0.95
Housing	\$110.71	24" x 50'	\$0.0077	in <sup>2</sup>	294	\$2.26	294	\$0.0077	\$2.26
Additives	\$65.60	500 g	\$0.13	g	150	\$19.68	150	\$0.13	\$19.68
Water Conduit	\$152.00	1500'	\$0.10	ft	1500	\$152.00	143	\$0.010	\$1.45
Lithium Hydride	\$16.00	1000 g	\$0.016	g	3000	\$48.00	3000	\$0.016	\$48.00
Dessicant	\$66.88	230,350 in <sup>3</sup>	\$0.00029	in <sup>3</sup>	5	\$0.00	5	\$0.00029	\$0.00
Plastic Valve	\$6.69	1	\$6.69		1	\$6.69	1	\$6.69	\$6.69
Plastic Hose	\$1.75	1	\$1.75		1	\$1.75	1	\$1.75	\$1.75
Plastic Nozzle	\$2.00	1	\$2.00		1	\$2.00	1	\$2.00	\$2.00
<b>Total</b>						<b>\$233.33</b>			<b>\$82.78</b>

- Main material cost drivers are the conduits and LiH
- Phase II material cost expectation of \$83 in relatively low procurement volumes
- Supports a H<sub>2</sub> refueler sale price of \$150-200

# Technology Status Today

---

- Phase I DOE program has shown the technical feasibility of the hydrogen refueler
  - Demonstrated mechanisms to gravity feed water to the conduits
  - Showed conduits and operational methods that increase the water vapor transport rate through the conduits
  - Showed using wick additives to increase the depth that water can diffuse through LiH and LiOH toward 100% LiH conversion
  - Demonstrated using a limited number of liquid water-LiH cells to bootstrap the reactor to 80 °C
  - Showed that only H<sub>2</sub> and water exit the refueler where a desiccant will adsorb the water before filling the fuel cell vehicle
  - Demonstrated material compatibility over 9 months supporting a long storage shelf life
  - Examined scale up using compartmented zones for heat removal and safe operation
  - Showed low material cost projections of \$83

# H<sub>2</sub> Refueler Technology into the Future

---

- DOE SBIR Phase II Program will be used to focus on further development of technology including:
  - Improving water conduit permeation and cost reduction via investigation into new materials and designs
  - Continued scaling of reactor to higher H<sub>2</sub> flow rates by increasing number of water conduits
  - Optimize design of water delivery system and thermal management
  - Investigate manufacturing requirements of various refueler components
  - Produce and demonstrate a 750 g H<sub>2</sub> refueler
  - Work with DOE/industry partners to obtain refueler specifications