



# High-Performance Ultralow-Cost Non-Precious Metal Catalyst System for AEM Electrolyzer

**P. I. Hoon T. Chung**  
**Los Alamos National Laboratory**

Project ID p158

This presentation does not contain any proprietary, confidential, or otherwise restricted information



# Project Overview

## Project Partners

Hoon T. Chung, Los Alamos National Laboratory  
Barr Zulevi, Pajarito Powder, LLC


## Project Vision

The key challenge in anion exchange membrane (AEM) electrolyzer is to achieve high performance without feeding any salt or alkaline solutions to the electrodes. In this project, we are developing PGM-free OER catalyst with high performance in the alkaline solution-free AEM water electrolyzer.

## Project Impact

By eliminating most expensive PEM electrolyzer components, AEM technology offers > 75% stack cost reduction. This opens a pathway to meeting the DOE H<sub>2</sub> production cost target of < \$2/kg.

Award #	2.2.0.402
Year 3 Start Date	10/01/2019
Year 3 End Date	09/30/2020
Year 3 DOE Share*	\$250 K
Year 3 Cost Share	\$ 28 K
Year 3 Total Funding	\$278 K



\* this amount does not cover support for HydroGEN resources leveraged by the project (which is provided separately by DOE)



# Approach- Summary

## Project Motivation

Since early 2000s, LANL has contributed significantly in the design and performance of PGM-free cathode catalysts for PEFCs. Pajarito Powder, LLC (PPC) is a venture-backed US manufacturer of electrochemical materials including catalysts. Leveraging expertise of both institutions, this project has been initiated.

## Barriers

- Cost:
  - ✓ Expensive materials: platinized titanium flow filed; Nafion® membrane; PGM-catalysts for PEM electrolyzers
  - ✓ Efficiency: High overpotential for HER and OER catalysts

## Key Impact

Metric	State of the Art	Proposed
AEM water electrolyzer performance	2.7 A/cm <sup>2</sup> at 1.8 V	2.8 A/cm <sup>2</sup> at 1.8 V
AEM water electrolyzer durability	Degradation rate of 1.7 mV/hr for ~ 200 hours at a current density of 200 mA/cm <sup>2</sup> with NiFe PGM-free catalyst	Degradation rate of 0.1 mV/hr for ~ 500 hours at a current density of 400 mA/cm <sup>2</sup> with perovskite PGM-free catalyst

## Partnerships

PPC is a partner of this project. Their expertise is in (i) mass-production of catalysts, (ii) fabrication of MEAs, and (iii) AEM electrolyzer test. Catalyst developed by LANL will be tested by PPC in AEM electrolyzer and be produced scaled-up of 25 g/batch.




# Relevance & Impact: H<sub>2</sub> Production for <\$2/kg

- AEM electrolysis vs. *PEM electrolysis*: significant cost reduction:

- ✓ PGM catalysts → PGM-free catalysts
- ✓ Titanium bipolar assembly → stainless steel bipolar assembly
- ✓ Nafion® perfluorinated membrane → hydrocarbon membrane

K. Ayers, AMR presentation PD094, 06/2014

PEM electrolyzer stack cost breakdown



- Bipolar assembly and MEA represents highest cost of PEM stack
- Alkaline media enables transition from titanium to stainless steel: eliminates 75% of part cost and also enables lower cost catalysts



- AEM electrolysis vs. *Alkaline electrolysis*: compact size; less corrosive environment:

- ✓ Corrosive alkaline solution → water
- ✓ Low gas purity → high gas purity
- ✓ Low current generation → high current density

**AEM water electrolysis has combined advantages of both PEM and alkaline electrolysis: the best system to meet the H<sub>2</sub> production cost target of < 2 \$/Kg of H<sub>2</sub>**



# Relevance: Development of Pure Water-feed AEM Electrolyzer



**Alkaline solution-feed leads to higher AEM electrolyzer performance compared to water-feed AEM electrolyzer → Development of high performance water-feed AEM electrolyzer is challenging.**





# FY20 Quarterly Progress Measures

Date	Quarterly Progress Measures	Status
December 2019 (Fy20 Q1)	Optimize test conditions for catalyst/ionomer interactions using ambient pressure x-ray photoelectron spectroscopy (XPS)	<b>Completed</b> (see slide **)
March 2020 (Fy20 Q2)	Synthesize perovskite OER catalyst that has particle size < 10 nm using a supercritical drying method, and demonstrate 500 mA/cm <sup>2</sup> at 1.8 V in a pure water-feeding (e.g., no added salt or base) AEM electrolyzer. The durability target is 0.5 mV/hr.	<b>Performance and durability targets met and exceeded</b> (see slides 10, 11)
June 2020 (Fy20 Q3)	PPC delivers 25 gr batch of scaled up catalyst that is developed by LANL with higher than 25 m <sup>2</sup> /gr BET surface area and activity great than 90% of small batch scale catalysts.	<b>On track</b>
September 2020 (Fy20 Q4)	Demonstrate 1 A/cm <sup>2</sup> at 1.8 V in a pure water-feeding (e.g., no added salt or base) AEM water electrolysis with PGM-free, carbon-free OER catalyst. The durability target is 0.1 mV/hr based on testing for 500 hour at a current density of ≥400 mA/cm <sup>2</sup> .	<b>On track</b>




# Accomplishment : Ionomer Effect and Ni-Mesh PTL



- 3 - Electrode "Flag" type electrode testing of catalyst/Ionomer/PTL interactions
- Ionomer significantly impacts OER performance
- Ni-mesh porous transport layer (PTL) exhibits much higher OER performance than expensive titanium(Ti) PTL → Ni PTLs to be employed in AEM electrolyzer



# Accomplishments: Catalyst Scale Up




- Catalyst technology is transferred to Pajarito Powder from LANL and scale upsynthesis preliminary results are demonstrated
- OER performance of LSC catalysts synthesized by Pajarito Powder match or exceed LANL LSC catalyst performance






# Accomplishment: Catalyst-Ionomer Interaction Effect

FLN1





4TMHA-DAPP-1



- FLN1 demonstrates higher initial performance but lower durability than 4TMHA-DAPP-1 → indicating understanding the catalyst-ionomer interaction critical particularly for durability



# Accomplishment: AEM Electrolyzer Performance




- Higher IEC ionomer (4TMHA-DAPP-2) enhances AEM electrolyzer performance than lower IEC ionomer (4TMHA-DAPP-1)
- Temperature has a huge impact on AEM electrolyzer performance
- Current density of 1.04 A/cm<sup>2</sup> is achieved at 1.8 V at 85°C




# Accomplishment: AEM Electrolyzer Durability

State-of-the-art durability with PGM-free catalyst





Y. S. Kim *et al* **10.1038** *Nature Energy* (2020)



- ~0.2 mV/hr degradation rate is demonstrated at 200 mA/cm<sup>2</sup> after initial pre-conditioning for 100 hour durability test with LSC-4TMHA-DAPP-2 catalyst-ionomer
- LSC-4TMHA-DAPP-2 catalyst-ionomer demonstrates higher performance and durability than state-of-the-art NiFe-TMA-53 catalyst-ionomer






# Accomplishment: Progress since FY19 AMR



- Noticeable progress in AEM performance and durability have been achieved since FY19 AMR



# Accomplishment: Catalyst-Ionomer Interaction




D. Li *et al* **116**, F1096 *ACS Appl. Mater. & Interface* (2019)

- Two ionomer degradations, (i) phenyl oxidation (ii) Hoffman elimination, are identified by  $^1\text{H NMR}$  for BPN ionomer in the durability tested AEM → causes for AEM performance degradation
- Catalysts impact phenyl oxidation significantly
- Catalyst – ionomer interaction is key parameter for improving performance and durability of AEM electrolyzers



# Collaboration: Effectiveness

## HydroGEN nodes utilization







Node	PI	Task
Separator for Hydrogen Production	Cy Fujimoto (SNL)	Anion exchange membranes and ionomer synthesis
In situ Testing Capabilities for Hydrogen Generation	Guido Bender (NREL)	AEM water electrolysis test
Surface Analysis Cluster Tool	Craig Perkins (NREL)	Composition analyses for fresh and tested AEM electrolyzer electrodes with XPS/UPS
PEC In Situ and Operando Testing Using X-rays	Walter Drisdell (LBNL)	In situ and operando characterization of catalyst/ionomer-membrane interfaces
Near Ambient Pressure Electrochemical X-Ray Photoelectron Spectroscopy	Anthony McDaniel (SNL)	Catalyst/ionomer interaction phenomena study in conjunction with electrochemical characterization



# Collaboration: Near Ambient Pressure Electrochemical XPS

**SNL node:** Catalyst/ionomer interaction phenomena study in conjunction with electrochemical characterization









- Ionomers impact metal element XPS → AP- electrochemical XPS experiments to correlate the XPS results to electrochemical activities are going to be tested



# Collaboration: In Situ and Operando XAS Study

**LBNL node:** In situ and operando characterization of catalyst/ionomer-membrane interfaces

**Catalyst:**  $\text{LaSrCoO}_3$   
**Ionomer:** 4TMHA-DAPP-1



- Catalyst/ionomer ratio optimization has been finished → In situ operando XAS experiments to correlate the XPS results to electrochemical activities are going to be measured





# Collaboration: In Situ and Operando XAS Study

**NREL node:** AEM water electrolysis test

**Anode:** LSC 6 mg/cm<sup>2</sup>

**Cathode:** PtRu/C; 1.0 mg<sub>Pt</sub>/cm<sup>2</sup>

**Ionomer:** 4TMHA-DAPP-1



- Lower performance and durability are measured in NREL than in LANL  
→ Gap study is in progress



# Proposed Future Work

- **Fundamental study**

- ✓ Understanding obtained from the AP XPS and in situ XAS will be utilized in catalyst optimization
- ✓ Gap study in AEM electrolyzer performance and durability between LANL and NERL will be done

- **Catalyst development**

- ✓ Supercritical method will be employed to reduce particle size of LSC
- ✓ PPC will deliver 25 gr batch of catalyst that is developed by LANL with higher than 25 m<sup>2</sup>/gr BET surface area and activity great than 90% of small batch scale catalysts

- **AEM electrolyzer test**

- ✓ Ni-mesh porous transport layer (PTL) exhibits much higher OER performance than expensive titanium(Ti) PTL → Ni PTL is going to be employed in AEM electrolyzer
- ✓ Achieved the durability target of 0.1 mV/hr based on testing for 500 hour at a current density of  $\geq 400$  mA/cm<sup>2</sup>



- **AEM water electrolyzer**

- ✓ Demonstrated significantly improved AEM water electrolyzer performance since FY19 AMR from 243 mA/cm<sup>2</sup> to 1087 mA/cm<sup>2</sup> at 1.8 V
- ✓ Excellent durability, ~ 0.2 mV/hr at 200mA/cm<sup>2</sup> , achieved at 60°C for 100 hours water-feed test
- ✓ Ni mesh PTL demonstrates promising GDE electrochemical cell performance and durability

- **Catalyst-Ionomer Interaction**

- ✓ FLN1 demonstrates higher initial performance but lower durability than 4TMHA-DAPP-1 → Understanding the catalyst-ionomer interaction is critical particularly for durability
- ✓ Catalyst/ionomer ratio optimization for in situ operando XAS has been finished → In situ operando XAS experiments to correlate the XPS results to electrochemical activities are going to be tested
- ✓ Ionomers change metal element XPS → AP- electrochemical XPS experiments to correlate the XPS results to electrochemical activities are going to be measured



- **Publication**

- Dongguo Li, Eun Joo Park, Wenlei Zhu, Qiurong Shi, Yang Zhou, Hangyu Tian, Yuehe Lin\*, Alesey Serov, Barr Zulevi, Ehren Donel Baca, Cy Fujjmotr, Hoon T. Chung, Yu Seung Kim\*, “Highly quaternized polystyreneionomers for high performance anion exchange membrane water electrolyzers” *Nature Energy*, **2020**, <http://doi.org/10.1038/s41560-020-0577-x>

\* corresponding authors

- **Presentations**

- Hoon T. Chung, “High Performance Ultralow-cost Non-Precious metal catalyst system for AEM Electrolyzer,” Poster presentation at the DOE Hydrogen and Fuel Cell Program Annual Merit Review, Washington, D.C., April 2019
- Hoon T. Chung et al., “Highly Active and Durable Perovskite OER Catalyst for Pure Water Anion Exchange Membrane Electrolysis ” 236<sup>th</sup> ECS Meeting, Atlanta, GA October 2019